

DECLARATION OF PERFORMANCE

Nr: 10251 en

1. Unique identification code of the product-type:

Wafer head screw sharp point, for wood/steel joists

(Surface treatment: phosphated, bright zinc plated, painted, Dacro 500 hr)

Dimension:

4,2xL (L = 13 - 65 mm)

4,8xL (L = 75 - 100 mm)

2. Article number:

413330, 513320, 513322, 513324, 513326, 513332, 513334, 513350, 513354, 571113, 571125,
572113, 572125, 572133, 572151, 572165, 572613, 572616, 572619, 572625, 572632, 572638,
572645, 572650, 573613, 573619, 573625, 573626, 573627, 573628, 573629, 573632, 573650,
573652, 575100, 575185, 575613, 575625, 578175, 10003707, 10003708, 10003709, 10003710,
10003711, 10003712, 10003713

3. Intended use:

Screws intended for the fixing of gypsum plasterboard (or gypsum boards with fibrous reinforcement) to timber and metal (recommended mounting depth 10 mm) in building construction works. They can also be used for the construction of the framing and for the connection between substructure and load bearing components and for fixing boards together, in accordance with EN 14566:2008+A1:2009.

4. Manufacturer:

ESSVE Produkter AB

Box 7091

SE 164 07 Kista

Sweden

Mail: info@essve.se

5. System of AVCP:

System 4

6. Notified body:

N.A

7. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14566:2008+A1:2009 Table ZA.1
Flexural strength	pass	EN 14566:2008+A1:2009 Table ZA.1

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Lisa Frode, Product Developer

Kista 2023-10-25